

## ATF POWER DX II

### Automatic transmission fluid

**ATF POWER DX II** is a high quality universal fluid to be used in automatic transmission, torque convertors and power steering of passenger cars, light vans and commercial vehicles.

**ATF POWER DX II** is formulated on high quality re-refined mineral- and synthetic base oil in combination with an unique additive package to reach the following properties:

- Good thermo- and oxidation stability.
- Controlled frictional characteristics for a smooth shift in a variety of driving conditions.
- Improved anti-wear, antirust and anticorrosion technology.
- High Viscosity Index ensures adequate lubrication in both high operating & low starting temperatures.
- Better foam control which leads to smooth & lasting shift feel and reduces fluid loss.
- Enhanced Low temperature fluidity which assists in good cold start performance.
- Compatible with all common seal materials.

**ATF POWER DX II** meets the following performance criteria:

GM Dexron II-D      MAN 339 type V1      MAN 339 type Z1      MB 236.9  
Voith H55.6335.xx      ZF TE-ML 03D/04D/14A/17C

### Typical Analysis

Properties	Unit	Method	Typical Value
Color		Visual	Red
Density @15°C	kg/m <sup>3</sup>	ASTM 4052	852
Kinematic Viscosity @ 40°C	mm <sup>2</sup> /s	ASTM D7042	36.4
Kinematic Viscosity @ 100°C	mm <sup>2</sup> /s	ASTM D7042	7.5
Viscosity Index		ASTM D2270	178
Viscosity Brookfield @-40°	cP	ASTM D2983	18.000
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-51
Date Issued: 26-1-2021		Supersedes: 26-09-2018	Revision Nr.: 04

